
## NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Heat-Load Simulator for Heat Sink Design



In the design of heat dissipating surfaces (heat sinks) for mounting heat generating electronics equipment, actual loading of the developmental heat sink with equipment design loads is a requirement. To operate complex, sophisticated, and expensive electronic gear merely for the purpose of designing heat dissipative mounts, is a poor approach to the problem from an economic as well as a time scheduling point of view. Because manufacturers rate components as to thermal output, simulated heat loading could be substituted

for actual component loading if close thermal output is assured.

A method has been found that provides a closely controlled thermal output to simulate actual electronic component thermal output in whatever configuration the actual installation will assume. The heat-load simulator is fabricated from 1/4-inch aluminum plate with a contact surface equal in dimensions and configuration to those of the electronic installation. On the opposite side of the plate thermocouple wire insulated

(continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States

Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

with glass fibers is arranged in a series of patterns and in sufficient depth to reproduce the thermal inputs to the mount that the final installation components would present. The above figure is an example of such a heat-load simulator designed in accordance with the thermal map shown below.

## Notes:

1. This innovation would make an excellent laboratory tool wherever cost and scheduling prohibits the use of actual electronic equipment. 2. Documentation for the innovation is available from:
Clearinghouse for Federal Scientific
and Technical Information
Springfield, Virginia 22151
Price \$3.00
Reference: B68-10510

## Patent status:

No patent action is contemplated by NASA.

Source: Ann M. Dunleavy
and Thomas J. Vaughn
of North American Rockwell Corporation
under contract to
Manned Spacecraft Center
(MSC-15170)

